


# Product data sheet

FLINDT BOLLARD 1100MM LED 3000K 15W ALU COL TEXT  
5747836260  
LOUIS POULSEN



Flindt Bollard Design by: Christian Flindt Light concept: The fixture emits an asymmetrical non glaring wide light directed downwards. The light creates an organic pattern on the surface where the bollard is mounted. Finish: Aluminium coloured or corten coloured. Textured surface, powder coated. Materials: Top: Cast aluminium. Reflector part: Cast aluminium. Post: Extruded aluminium. Base plate: Cast aluminium. Mounting: Terminal block position: In the top. Looping: Approved, max. 5x6mm<sup>2</sup>. Driver position: In the top. Post f/in ground installation: H: 1700mm incl. fixture head, in ground part 600 or 900mm. Post w/anchorage unit: H: 1110/1410mm incl. fixture head, in ground anchorage unit 310mm. Post w/base plate for surface mounting: H 800/1100mm incl. fixture head. Post dia. Ø115mm. Sizes and weights: Width x Height x Length (mm) 280 x 800 x 280 Max 9.8 kg 280 x 1100 x 280 Max 11.0 kg 115 x 1100 x 115 Max 10.9 kg 115 x 800 x 115 Max 9.7 kg Class: Ingress protection IP65. Electric shock protection I w. ground, II w/o ground. IK10.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	80
Total flux	578 lm	LOR	100%
Luminous efficacy	39 lm/W	ULOR	6%
		Total power	15 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 4.80 in

Width: 4.53 in

Height: 43.31 in

## Adjustability

Fixed

## Electric

System power: 15 W

Appliance Class: II

## Protection

IP: 65

IK: 10