

Product data sheet

FLAT POLYMERO KREIS
311977.002.2.76
RZB




IP
40

IK
10

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (polycarbonate). Diffuser fastening: push lock. Available Colours: white
Type of Installation: Pendant Dimensions: D 360, H 87 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: AC power, DALI dimmable Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1300lm System power: 13W Beam Angle: 122° Number of fittings B10A: 131 Number of fittings B16A: 210 Number of fittings C10A: 131 Number of fittings C16A: 210 Inrush current: 0,1A Unified Glare Ratio: 19,0 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	13%
		Total power	13 W

Mounting mode

Pendant

Electric

System power: 13 W

Shape and measurements

Height: 3.43 in
Diameter: 14.17 in

Protection

IP: 40
IK: 10

Adjustability

Fixed