


Product data sheet

RTEC L13 R E3
RTEC EMERGENCY
DEXTRA




Rapid Tec - Ø174mm, C84, IP20 Recessed downlighter with polycarbonate bezel, sprung steel mounting clips, anodised aluminium reflectors available in semi-specular or specular. Options: E3 - Emergency control gear (609 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) C83 - CRI 80, 3000K

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	609 lm	LOR	100%
Luminous efficacy	203 lm/W	Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9.1 W	CRI	80
Total flux	1130 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	9.1 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.44 in
Diameter: 6.77 in

Adjustability

Fixed

Electric

System power: 12.1 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 40
Designation labels: CE