

# Product data sheet


KAP 105  
03.4400.74/QT-12/20W/35W/50W  
FLOS



IP  
44


Luminaire with embedded installations on ceilings for halogen lamps, metal halide and LED. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

## Light output 1




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	20 W	Socket	E27
Lamp flux	300 lm	LOR	18%
Luminous efficacy	3 lm/W	Total flux	54 lm
CCT	2756 K	Total power	20 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gy6.35
Lamp flux	600 lm	LOR	18%
Luminous efficacy	3 lm/W	Total flux	109 lm
CCT	3000 K	Total power	35 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gy6.35
Lamp flux	910 lm	LOR	18%
Luminous efficacy	3 lm/W	Total flux	165 lm
CCT	3000 K	Total power	50 W
CRI	99		

## Mounting mode

Ceiling recessed

## Electric

System power: 20-50 W

### Shape and measurements

Height: 7.28 in

Diameter: 4.13 in

### Adjustability

Fixed

### Protection

IP: 44