# Product data sheet

LAM4B 4-INCH NEW CONSTRUCTION RECESSED MULTI-HEAD

LAMR4B412R209727DE01021MW


COOPER LIGHTING





Distributions: 10° - 70°; Optic holds 2 lens media, Lockable 365° rotation and 45° tilt holds any aiming position, Downlight, accent, and pinhole reflectors;, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 90 or 97; D2W<sup>™</sup> option from 3000K to 1850K, Lumens: 800 and 1000, Matte black, matte white, and matte metallic silver paint finishes, 0-10V 1% dimming driver; Optional 100%-1% DALI, 0-10V, or DMX drivers, Mud in accessory for seamless transition, Wavelinx and DLVP connected systems; 5-year warranty

#### Light output 1 (integrated)



| Lamp type          | LED     | CCT         | 3000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 54.1 W  | CRI         | 100    |
| Total flux         | 5027 lm | LOR         | 100%   |
| Luminous efficacy  | 93 lm/W | Total power | 54.1 W |

## Mounting mode

Ceiling recessed

### Shape and measurements

Height: 0.39 in Diameter: 2.00 in

## Adjustability

Fixed

### Electric

System power: 54.1 W

## Protection

IP: 47