

# Product data sheet


MODERN PENDANTS  
FL2199/6/887  
FRANKLITE



IP  
20


1120mm Spreader for Glass Chrome finish 6lt spreader ring with 2m clear cables for adjustment on site

## Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	9 W	CRI	80
Total flux	733 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	46%
		Total power	9 W

## Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	9 W	CRI	80
Total flux	733 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	46%
		Total power	9 W

## Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	9 W	CRI	80
Total flux	733 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	46%
		Total power	9 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	9 W	CRI	80
Total flux	733 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	46%
		Total power	9 W

Light output 5 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	9 W	CRI	80
Total flux	733 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	46%
		Total power	9 W

Light output 6 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	9 W	CRI	80
Total flux	733 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	46%
		Total power	9 W

Mounting mode

Pendant

Shape and measurements

Length: 56.98 in

Width: 53.33 in

Height: 73.80 in

Adjustability

Fixed

Electric

System power: 54 W

Protection

IP: 20