Product data sheet


SCAPHA 311992.004.1.76 RZB





Series: SCAPHA Pendant luminaire with elliptical shape. Base: aluminium, powder-coated. Canopy and glass fixture steel powder-coated. Handmade concave glass, matt finish on the outside, painted white on the inside. Uniform and glare-free illumination of the small boat shaped corpus by specially adapted LED panel boards. Suitable for pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. TouchDim sensor capable. Light and/or presence sensors can be integrated. Colour: silver, metallic Length: 1264 mm Width: 174 mm Height: 66.5 mm Suspension length: 500-1200 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 51 W Rated luminous flux: 3550 lm Luminous efficiency: 70 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type Nominal lamp power Total flux Luminous efficacy

| LED | |
|---------|--|
| 51 W | |
| 3550 lm | |
| 70 lm/W | |
| | |

| CCT | 4000 K |
|-------------|--------|
| CRI | 80 |
| LOR | 100% |
| ULOR | 11% |
| Total power | 51 W |

Mounting mode

Pendant

Shape and measurements

Length: 6.85 in Width: 49.76 in Height: 2.64 in

Adjustability

Fixed

Electric System power: 51 W

Protection

IP: 20