

Product data sheet

HB 506
221189.002.2
RZB




IP
20


IK
06

Series: HB 506 Ceiling and wall luminaire with slim design. Housing: plastic (polycarbonate). Diffuser: plastic (polycarbonate), opal. Base and diffuser are sealed together. MultiColour: Colour temperature adjustable via switching element. Choice of 3000K or 4000K. Factory setting is 3000K. Quick mounting adapter galvanized steel sheet, with fastening screws. Driver integrated. Colour: white
Length: 260mm Width: 260mm Height: 53mm Lamp: LED Socket: without socket Colour temperature: 3000K, 4000K
Colour rendering index (CRI): 80 System power: 18W Rated luminous flux: 1700lm Luminous efficiency: 94lm/W System power 2: 18W Rated luminous flux 2: 1800lm Luminous efficiency 2: 100lm/W Control gear: EB Protection class: I Type of protection: IP20

Light output 1



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1800 lm	ULOR	9%
Luminous efficacy	100 lm/W	Total flux	1800 lm
CCT	4000 K	Total power	18 W
CRI	80		



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1700 lm	ULOR	9%
Luminous efficacy	94 lm/W	Total flux	1700 lm
CCT	3000 K	Total power	18 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 10.24 in

Width: 10.24 in

Height: 2.09 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 20

IK: 06