


Product data sheet

PH 3½ - 2½ FLOOR E27 LED 2700K 7W
5744162199
LOUIS POULSEN



PH 3½-2½ Floor Design : Poul Henningsen Concept : The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of hand-blown opal three-layer glass, which is glossy on top and sandblasted matte on the underside, giving a soft and diffuse light distribution. Finish : High lustre chrome plated. White opal glass. Material : Shades: Mouth-blown white opal glass. Top plate: High lustre chrome plated, spun brass. Base: High lustre chrome plated, spun brass. Stem: High lustre chrome plated, steel. Mounting : Cable type: Plastic cord with plug. Cable length: 2.5m. Light control: On/off switch on cord. Class : Ingress protection IP20. Electric shock protection II w/o ground. Weight : Max. 7.5kg.

Light output 1



1 x LED			
Nominal lamp power	7 W	LOR	70%
Lamp flux	806 lm	ULOR	19%
Luminous efficacy	81 lm/W	Total flux	567 lm
CCT	2700 K	Total power	7 W
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 12.99 in
Width: 12.99 in
Height: 50.87 in

Adjustability

Fixed

Electric

System power: 7 W
Appliance Class: II

Protection

IP: 20