


# Product data sheet

LIGHT LINEAR VT 2 BOLLARDS  
VT-10012-T3-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53 W	CRI	80
Total flux	5245 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	15%
		Total power	53 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53 W	CRI	80
Total flux	5245 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	15%
		Total power	53 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 4.88 in

Width: 7.87 in

Height: 39.37 in

Weight: 9.9 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 106 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 07

Surface temperature: 40°C