


# Product data sheet

CALANDO BRUSHED STEEL 650LM 3000K RA>80 TRAILING EDGE DIMMING  
7021982975141  
SG ARMATUREN



Round LED ceiling lamp with diffuser made of frosted glass. Good solution for entrances and corridors. The whole luminaire has been approved for common access routes. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Light distribution Direct Light technic LED 11W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP44 Materials and finish Housing: Aluminium Colour: Brushed steel Optics: Glass Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1



1 x LED			
Nominal lamp power	11 W	LOR	100%
Lamp flux	650 lm	ULOR	11%
Luminous efficacy	59 lm/W	Total flux	650 lm
CCT	3000 K	Total power	11 W
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 11.14 in  
Width: 11.14 in  
Height: 3.92 in

## Adjustability

Fixed

## Electric

System power: 11 W  
Appliance Class: II

## Protection

IP: 44