Product data sheet


NADJA I (WALL FITTING) 9.840.3066.05 LEIPZIGER LEUCHTEN




Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

IP 55

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR	77%		
Lamp flux	6800 lm	Total flux	5247 lm		
Luminous efficacy	38 lm/W	Total power	137 W		
CCT	3400 K				
CRI	54				



1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	77%		
Lamp flux	4000 lm	Total flux	3087 lm		
Luminous efficacy	35 lm/W	Total power	89 W		
CCT	3400 K				
CRI	54				

Mounting mode	Electric
Wall mounted	System power: 89-137 W
Shape and measurements	Protection
Height: 20.08 in	IP: 55
Diameter: 20.08 in	