
Product data sheet

SMART LOTIS 82 LED GE 4000K FLOOD BLACK STRUC 12441332


MODULAR







Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module (LED, halogen or discharge) which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. Smart Lotis comes with the typical Lotis cup. Choose from a white or black structure.

Light output 1







Mounting mode

Ceiling recessed

1 x LED			
Nominal lamp power	13.4 W	LOR	91%
Lamp flux	1018 lm	Total flux	930 lm
Luminous efficacy	69 lm/W	Total power	13.4 W
CCT	4000 K		
CRI	90		
1 x LED			
Nominal lamp power	6.2 W	LOR	91%
Lamp flux	630 lm	Total flux	575 lm
Luminous efficacy	93 lm/W	Total power	6.2 W
CCT	4000 K	i otar power	0.2 W
CRI	90		
OTT	30		
1 x LED			
Nominal lamp power	9.2 W	LOR	91%
Lamp flux	792 lm	Total flux	723 lm
Luminous efficacy	79 lm/W	Total power	9.2 W
CCT	4000 K		
CRI	90		

Created by luminaires.dialux.com (8 May, 2024)

Shape and measurements

Height: 0.39 in Diameter: 3.23 in

Adjustability

Fixed

Electric

System power: 6.2-13.4 W Appliance Class: II

Protection

IP: 20