


Product data sheet

PLUTO - SLIM RAMP
6015-0-3-669-XX
UNILAMP



Wall recessed fixtures PLUTO is available with SMD LED light source in 3000K and 4000K color temperature. PLUTO – Ramp is used as a functional guide fitting for path or driveway with downward light flow without a glare. The glass diffuser is not visible at low level and it is IP65 rated. PLUTO – Flat is assembled with a unique white-coated tempered glass and illuminates not only the ground surface but also its surroundings. The slim-recess housing enables it to be installed in thin wall applications. This wall recess family has a minimal design so it can be used in modern architectural environments. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-2 and VDE regulations. • LM6 die-cast aluminium body. • GFR polymer recess box. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	35%
Lamp flux	3040 lm	Total flux	1057 lm
Luminous efficacy	190 lm/W	Total power	17 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall recessed

Shape and measurements

Length: 9.84 in

Width: 4.13 in

Height: 10.83 in

Adjustability

Fixed

Electric

System power: 17 W

Appliance Class: I

Protection

IP: 65

IK: 07