Product data sheet

SPIKE GRAPHITE UPLIGHT TWILIGHT 840LM 3000K RA>80 ON/OFF 7021986239232

SG ARMATUREN












Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct/Indirect Light technic LED 17W (11W+6W) 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class I IP44 IK08 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Graphite Optics: Polycarbonat (PC) Mounting/Connection Surface, Outdoor Screwless terminal block

Light output 1



1 x LED			
Nominal lamp power	17 W	LOR	
Lamp flux	890 lm	ULOR	
Luminous efficacy	52 lm/W	Total flux	
CCT	3000 K	Total power	
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 6.53 in Width: 6.01 in Height: 6.69 in

Adjustability

Fixed

Electric

System power: 17 W Appliance Class: I

Protection

IP: 44 IK: 08

100% 7% 890 lm 17 W