


# Product data sheet

GUSTAV I (W. SHIELD ON SIDE FACING BUILDING)  
9.681.2052.27  
LEIPZIGER LEUCHTEN



Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	100 W	LOR	50%
Lamp flux	10400 lm	ULOR	10%
Luminous efficacy	45 lm/W	Total flux	5153 lm
CCT	2000 K	Total power	115 W
CRI	25		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 29.13 in

Diameter: 9.84 in

## Design

Material impression: Matt

Color of housing: White

## Electric

System power: 115 W

Ballast: ECG

## Integrated sensors

Integrated sensors: Motion sensor

## Protection

IP: 55

Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...95°F