Product data sheet

ATHLON OPTIC AREA LIGHT / DOUBLE SIDED 7259-I-5-897-XX

UNILAMP










ATHLON is a series of mini floodlights with wide beam asymmetrical and bi-symmetrical light distribution. It operates with High Power LED module which is attached on aluminium body as a heat sink. The Alanod Miro reflectors used in this luminaire are designed by Photopia high-end lighting engineering software. The calibrated aiming unit provides accuracy of the light distribution on the illuminated surface. The range of accessories such as ground mount spike, tree strap and pole clamping unit makes it a dynamic floodlight choice. ATHLON is suitable to light up small to medium sized objects or areas such as signage boards, ceiling, building facades, etc.

Light output 1



1	Χ	LED	
Ν	lo	mina	

Nominal lamp power 25 W
Lamp flux 2880 lm
Luminous efficacy 115 lm/W
CCT 3000 K
CRI 80

LOR Total flux

Total power


77% 2206 lm 28 W

77%

2206 lm

28 W

Light output 2



1 x LED

Nominal lamp power 25 W
Lamp flux 2880 lm
Luminous efficacy 115 lm/W
CCT 3000 K
CRI 80

LOR Total flux Total power

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 9.67 in Width: 4.13 in Height: 9.23 in

Adjustability

Rotatable, Tiltable

Electric

System power: 56 W Controller: DALI Appliance Class: I

Protection

IP: 66 IK: 07