

# Product data sheet

FLAT BASIC  
211400.002  
RZB




IP  
43

IK  
02

Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Diffuser fastening: spring system. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). Colour: pure white (RAL#160;9010) Diameter: 420#160;mm Height: 124#160;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 83 System power: 12#160;W Rated luminous flux: 1200#160;lm Luminous efficiency: 100#160;lm/W Control gear: AC Strom, dim.Ph.an-/abschnitt Protection class: I Type of protection: IP#160;43

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	16%
		Total power	12 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 4.88 in  
Diameter: 16.54 in

## Adjustability

Fixed

## Electric

System power: 12 W

## Protection

IP: 43  
IK: 02