

Product data sheet

ITZA DELTA SINGLE GREY S TW 2700-6500K - 27K CLO
16673-478_27K
FAGERHULT



Installation Wire suspension via bracket with friction lock, supplied with luminaire. Connection Single – Connections are made at the end of the luminaire and are concealed by the end-cap. 5-way snap-in terminal block at one end. Continuous installation – 5-way snap-in terminal block at each end and through-wiring cable 3Ø1.5 mm² as standard. With dimming, 5-way snap-in terminal block, 1-phase through-wiring possible. Design Luminaire body of sheet steel, white (RAL 9016) or alu-grey (RAL 9006) finish, end-caps in polycarbonate. The top is covered by an active film which generates a broad light pattern and which works as a dust cover. When continuous installation is required the luminaire is supplemented with continuous couplers and end-caps, see the accessory page. Louvre Delta – microprism louvre in acrylic (PMMA. Reflector The louvre act as a reflector.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	44 W	CRI	80
Total flux	4437 lm	LOR	100%
Luminous efficacy	101 lm/W	ULOR	50%
		Total power	44 W

Mounting mode

Pendant

Electric

System power: 44 W

Shape and measurements

Length: 48.97 in
Width: 4.89 in
Height: 3.72 in

Protection

IP: 20

Adjustability

Fixed

Design

Color of housing: Silver gray, White