
Product data sheet

LUCAS X (WALL FITTING) 9.833.3066.15 LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



H	"ATT
SXX	
$\land \lor \lor$	
XP	
XT	-t

1 x High pressure mercury vapour lamp

5 1 · · · · · · · · · · · · · · · · · ·					
Nominal lamp power	125 W	LOR	84%		
Lamp flux	6800 lm	Total flux	5697 lm		
Luminous efficacy	42 lm/W	Total power	137 W		
CCT	3400 K				
CRI	54				

1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	84%		
Lamp flux	4000 lm	Total flux	3351 lm		
Luminous efficacy	38 lm/W	Total power	89 W		
CCT	3400 K				
CRI	54				

Mounting mode	Electric
Wall mounted	System power: 89-137 W
Shape and measurements	Ballast: ECG
Height: 22.44 in	Integrated sensors
Diameter: 22.44 in	Integrated sensors: Motion sensor
Design	Protection
Material impression: Matt	IP: 55
Color of housing: White	Designation labels: CE
	Other operating numbers
	Ambient temperature range: 3286°F