



Product data sheet

LOUI 50
925343.0045.76
RZB



Series: LESS IS MORE 50;system Gerades Modulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Nur optional: Lichtbandsystem vorbereitet für Seilabhngung! Colour: silver, matt (approx. RAL9006) Length: 1121mm Width: 57mm Height: 75mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28W Rated luminous flux: 3350lm Luminous efficiency: 120lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	3350 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.24 m
Width: 44.13 mm
Height: 2.95 mm

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 20
IK: 03