Product data sheet

LUCAS XI (1-ARMED BEADED) 9.849.2152.16

LEIPZIGER LEUCHTEN









Mounting height 6.00 m. Other heights please inquire. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes reinforced and hot-galvanized triple offset Pole dia. 76 mm inclusive painted bracket made of spezial steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	47 lm/W	
CCT	2000 k	
CRI	25	

LOR	83%
ULOR	2%
Total flux	2901 lm
Total power	62 W



i x High pressure sodium vapour iamp		
Nominal lamp power	70 W	
Lamp flux	5600 lm	
Luminous efficacy	56 lm/W	
CCT	2000 K	
CRI	25	

LOR	83%
ULOR	2%
Total flux	4642 lm
Total power	83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 62-83 W

Protection

IP: 55