
# Product data sheet

FLAT POLYMERO 311626.002.5.76

RZB










Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Colour: white Diameter: 300 mm Height: 100 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 10 W Rated luminous flux: 1050 lm Luminous efficiency: 105 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 40

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	1050 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	15%
		Total power	10 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.94 in Diameter: 11.81 in

#### Adjustability

Fixed

## Design

Material impression: Matt Color of housing: Black

#### Electric

System power: 10 W Ballast: ECG

## Protection

IP: 40 IK: 03

Designation labels: CE

### Other operating numbers

Ambient temperature range: 14...95°F