# Product data sheet

ALDO 3 FLOODLINGHTS AND COLUMN PROJECTORS


ALD-30171-W-W40

LIGMAN



- Lamp LED - Colour 3000K and 4000K - Powder coated aluminium alloy housing - Adjustable stainless steel bracket - Two cable entries for through wiring - Bright and consistent distribution, with seamless treatment with continuous mounting - Constant voltage (CV) 24V - Remote driver is not included - DC24V input, DMX512 address with constant current control for RGBW products

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	48 W	CRI	80
Total flux	3190 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	48 W

## Mounting mode

Standing / Bollard, Ceiling mounted

### Shape and measurements

Length: 39.37 in Width: 3.03 in Height: 28.35 in Weight: 1.85 kg

### Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

#### Electric

System power: 48 W Voltage: 230 V AC Ballast: ECG Controller: Dimmable 1..10V, DALI Appliance Class: III

## Protection

IP: 65 IK: 08 Surface temperature: 40°C Designation labels: CE