

Product data sheet

亮影系列LED悬挂灯


PAK451310 PAK-LED-H01-050-840 (4头200W)

PAK




壳体:压铸铝; 反光罩:光学透镜+阳极氧化铝; 功率:200W; 光源:COB LED; 色温:4000K; 显色性:Ra80+; 光束角:80°; 灯具总输出流明:15200Lm; 使用寿命:30000Hrs; 防护等级:IP65; 适配电器:LED恒流驱动电源, 主电压:220V/50Hz; 产品尺寸 : Φ165*H300mm; 功率因数 : 0.95; 安装方式:吊钩式安装; 颜色:铝色+黑色。

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	50 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	50 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	50 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	50 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 13.93 in
Width: 13.87 in
Height: 12.42 in

Adjustability

Fixed

Electric

System power: 200 W

Protection

IP: 20