

Product data sheet


TOTO 2X28/54W DALI BRED. ACTILUME SENSOR
3382051
SOLAR



IP
23

ToTo Åpen industriarmatur 2x28 eller 54W DALI multireaktor i varmgalvanisert stål MIRO aluminium , 5x2,5mm² gjennomgangskobling


Light output 1



2 x Fluorescent lamp tubular T5

Nominal lamp power	54 W
Lamp flux	4450 lm
Luminous efficacy	74 lm/W
CCT	4000 K
CRI	85


Socket	G5
LOR	96%
Total flux	8503 lm
Total power	115 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	54 W
Lamp flux	4450 lm
Luminous efficacy	74 lm/W
CCT	3000 K
CRI	85


Socket	G5
LOR	96%
Total flux	8503 lm
Total power	115 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	28 W
Lamp flux	2600 lm
Luminous efficacy	79 lm/W
CCT	4000 K
CRI	85

Socket	G5
LOR	96%
Total flux	4968 lm
Total power	63 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	28 W	Socket	G5
Lamp flux	2600 lm	LOR	96%
Luminous efficacy	79 lm/W	Total flux	4968 lm
CCT	3000 K	Total power	63 W
CRI	85		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 52.76 in
Width: 6.89 in
Height: 2.95 in

Adjustability

Fixed

Electric

System power: 63-115 W

Protection

IP: 23