

Product data sheet

LUCAS VIII (1-ARMED)
9.858.2072.15
LEIPZIGER LEUCHTEN



IP
55

High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately, inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|----------|-------------|----------|
| Nominal lamp power | 150 W | LOR | 80% |
| Lamp flux | 17000 lm | ULOR | 4% |
| Luminous efficacy | 77 lm/W | Total flux | 13541 lm |
| CCT | 2000 K | Total power | 176 W |
| CRI | 25 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in

Diameter: 22.44 in

Electric

System power: 176 W

Protection

IP: 55