

Product data sheet


EDLR 195/2000-840 W + DR195-SBDR-G-SB-W
0321317 + 0202719
RIDI



IP
20

Recessed downlighter with LED Design: Recessed downlighter, diameter 195 mm with LED module, comprising reflector housing and gear tray. Fitted with RIDI LED module. Protection rating on the room side IP 40, ceiling side IP20. Reflector housing: Rigid mounting ring in die-cast metal with toolless fixing clips for ceiling mounting and reflector holding clips. Integrated fixture for toolless mounting of the decor ring and accessories. Decorative ring made of white polycarbonate with bayonet fitting. Functional module in white polycarbonate for mounting the reflector using the bayonet fitting. Diffusor made of transparent polycarbonate with internally satinised polycarbonate to protect the LED, clips into the functional module (opal diffuser available on request). Gear tray: Gear tray plate made of galvanised steel, accommodates the electrical components, mains connector block, cable strain relief and connecting cable to the LED module. Clip-on heat resistant polycarbonate cover. Gear tray 90 mm high in emergency lighting version. Electronic converter for LED, 220-240 Volt, 0/50-60 Hz and internal connector block 3x2.5mm². Suitable for direct voltage operation and use in central battery systems. Mounting: In addition to the standard fixing clips for clamping thicknesses from 0 to 25 mm, special accessory fixing kits such as panel mounting kits, reinforcement plates, cast concrete housings, plaster rings, inclined mounting kits or semi-recessed mounting kits can be ordered. EDLR 195/... W Diameter 195 mm. High-reflectance white reflector made of pure aluminium, powder coated similar to RAL9016. DR195-SBDR-G-SB-W Decorative safety glass, printed, with white decorative ring

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	83%
Lamp flux	2100 lm	Total flux	1735 lm
Luminous efficacy	108 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Electric

System power: 16 W

Shape and measurements

Length: 7.69 in
Width: 7.68 in
Height: 3.60 in

Protection

IP: 20

Adjustability

Fixed

Design

Color of housing: White