

# Product data sheet

VOLKMAR II (3-ARMED)

9.870.0210.05


LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection - Available in any RAL - or DB -colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


## Light output 1



### 1 x Compact fluorescent lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 42 W    | LOR         | 85%     |
| Lamp flux          | 3200 lm | ULOR        | 28%     |
| Luminous efficacy  | 59 lm/W | Total flux  | 2708 lm |
| CCT                | 2899 K  | Total power | 46 W    |
| CRI                | 90      |             |         |


## Light output 2



### 1 x Compact fluorescent lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 42 W    | LOR         | 85%     |
| Lamp flux          | 3200 lm | ULOR        | 28%     |
| Luminous efficacy  | 59 lm/W | Total flux  | 2708 lm |
| CCT                | 2899 K  | Total power | 46 W    |
| CRI                | 90      |             |         |

## Light output 3



### 1 x Compact fluorescent lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 42 W    | LOR         | 85%     |
| Lamp flux          | 3200 lm | ULOR        | 28%     |
| Luminous efficacy  | 59 lm/W | Total flux  | 2708 lm |
| CCT                | 2899 K  | Total power | 46 W    |
| CRI                | 90      |             |         |

**Mounting mode**

Pole top mounted

**Shape and measurements**

Height: 28.35 in

Diameter: 16.14 in

**Electric**

System power: 138 W

**Protection**

IP: 55