Product data sheet

CIRCULUS BLACK 19W LED 2700K RA>80 5046214000

SG ARMATUREN






L



Round surface-mounted luminaire, wholly uniform light with attractive design, made of powder-coated aluminium, simple to mount by removing the back plate, which can be screwed on to all known ceiling outlets/electrical boxes, clips with option of additional looping, connectors between lamp and mounting plate, dimmable driver phase-dimming/DALI and sensor options. Both visible and hidden cabling possible. Light distribution Direct Light technic LED (not exchangeable) 19W 2700K Ra>80 SDCM 3 L80/B10 >50,000 hrs at Ta=25°C L70/B50 >100,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP21 Energy and approvals A+ CE Materials and finish Housing: Steel Colour: Black (RAL 9004) Optics: PMMA Polymethylmethacrylat Mounting/Connection Surface, Indoor Screwless terminal block

Light output 1 (integrated)



LED	CCT	2700 K
19 W	CRI	80
1360 lm	LOR	100%
72 lm/W	Total power	19 W
	19 W 1360 lm	19 W CRI 1360 lm LOR

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.17 in Width: 14.17 in Height: 1.77 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 19 W Appliance Class: I

Protection

IP: 21