


Product data sheet

STAGE PROJECTOR

S.1325N

SIMES




Version is available on request. SPOTLIGHTS STAGE ROUND SPOT S.1325N 1 module COB 4000K 220-240Vac DIMMABLE DALI; DALI2; PUSH

Rated module luminous flux: 4936lm Rated luminaire luminous flux: : 3146lm Rated module power: : 31.1W Rated luminaire power: : 37W

Luminaire efficacy: : 85lm/W Voltage (AC): : 220-240Vac Frequency (AC): : 50/60Hz Voltage (DC): : 176-275Vdc (No PUSH DIM) Dimmable: : DALI; DALI2; PUSH PUSH Synchronization: - Max 4 Luminaires, distance <15m; - Max 35 Luminaires, distance <300m with S.2490 accessory.

Electrical insulation class: : II Protection class IP: : IP66 Mechanical resistance: : IK08 CE ENEC SPECIAL VERSION ON REQUEST: this Luminaires can be supplied with a surcharge in class III (without power supply). Requires working remote power supply in constant current at 900mA $V_{min}=31.2Vdc$ $V_{max}=36.8Vdc$. Example SIMES compatible power supplies (check the complete list of the drivers on the catalogue): Art. S.2410 POWER SUPPLY DALI2 230V/350-1050mA 57,8W IP67 Art. S.3427 POWER SUPPLY Dali, 1-10V, PUSH MULTI-POWER 230V/350mA-1050mA IP20 NB: Use 1 Power Supply for each Luminaires LUMINAIRE TYPE Projector. IP rating IP 66 MATERIAL CHARACTERISTICS Die-cast EN AB-47100 aluminium housing with high corrosion resistance. Stone wash surface treatment prior to painting process. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. Silicone gaskets. Painting Process : 3 Step Process 1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 08 LIGHTING PERFORMANCE 99.98% pure aluminium reflectors, or with concentrating lenses: The sophisticated optics focuses the beam and makes the light comfortable by reducing the direct glare of the light source. Clear toughened glass. LOR -- INSTALLATION AND MAINTENANCE The tempered front glass diffuser is fixed externally to the fitting through silicon resin, perfectly flush with the front ring. Water and dirt deposits that can disturb the lighting performance of the projector can easily flow away. WIRING Supply 0.4m cable section type FEP/FEP + PCP (Microstage and Ministage) or H05RN-F (Stage and Megastage) sealed with B component epoxy resin, wired internally protected by silicon sheaths. Stage/Megastage: Fast connector ($\varnothing 7\div 12$ mm) IP68 supplied as standard for single cable connection. Isolation: CLASS II . Available colours: Aluminium grey (cod.14), Anthracite grey (cod.24). Weight: 4.5205 Kg Glow Wire test: -- LED module included REGISTERED DESIGN MICROSTAGE BLADE OF LIGHT PATENTED, REGISTERED DESIGN This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user. This product contains a light source of energy efficiency class (EPREL - European Product Registry for Energy Labelling): E. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 70.000 hours Ta 25°C, min. 50,000 hours at 40°C. Performance Ambient temperature Tq 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C. ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE. We recommend installing surge protection devices "SPD" in the electrical system. Protection devices prevent the intensity of these phenomena's, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be carried out from the electrical designer and is not supplied by SIMES).

Light output 1 (integrated)



Lamp type	LED	CCT	3800 K
Nominal lamp power	36.1 W	CRI	86
Total flux	3066 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	36.1 W

Mounting mode

Wall mounted, Ceiling mounted, Floor mounted

Shape and measurements

Height: 5.56 in
Diameter: 5.32 in

Adjustability

Rotatable

Design

Material impression: Aluminum, Glass
Color of housing: Silver gray
Designer: SIMES S.P.A.

Electric

System power: 36.1 W
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE