Product data sheet

SANTOS KREIS 311715.0042.1

RZB







Series: Santos Kreis Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, white, powder-coated. Diffuser fastening: decorative ring with spring system. Diffuser: domed opal glass plate, frosted. Decorative ring: metal. Available Colours: nickel, matt Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 310, H 87 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 680lm System power: 14W Beam Angle: 114° Number of fittings B10A: 10 Number of fittings B16A: 27 Number of fittings C10A: 28 Number of fittings C16A: 45 Inrush current: 27A Unified Glare Ratio: 19,4 EEC: A+

Light output 1 (integrated)



| Lamp type | LED | CCT | 4000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 14 W | CRI | 80 |
| Total flux | 680 lm | LOR | 100% |
| Luminous efficacy | 49 lm/W | ULOR | 4% |
| | | Total power | 14 W |

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.43 in Diameter: 12.20 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 20