



# Product data sheet

AMEDH L30 LE3  
AMENITY DECORATIVE LED HALO EMERGENCY  
DEXTRA




Amenity Decorative Halo LED - IP40, IK08 Circular surface mounted luminaire, with soft halo effect, white polycarbonate bulkhead, opal polycarbonate diffuser available with various decorative rings. Options: LE3 - Lithium Emergency (238 lumens) LS3 - Lithium Selftest LA3 - Lithium Autotest A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* S - Switch Dimming D - Digital Dimming (DSI) R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode\* R25W - Reacta-Wave Wireless sensor DALI R25WE - Reacta-Wave Wireless sensor On/Off \*Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off. AMED SRB - Amenity semi recessing kit (330mm cut out) AMED AWR - Amenity decorative angled white ring AMED ACR - Amenity decorative angled chrome ring AMED ABR - Amenity decorative angled brass ring NL - Night Light (not available with Emergency version)

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	238 lm	LOR	100%
Luminous efficacy	60 lm/W	ULOR	6%
		Total power	4 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.7 W	CRI	80
Total flux	2345 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	6%
		Total power	19.7 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 5.12 in

Diameter: 13.78 in

## Electric

System power: 23.7 W

Ballast: ECG

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Adjustability

Fixed

## Protection

IP: 40

IK: 08

Designation labels: CE