


Product data sheet

DOUALA KRISTALL
311531.000.1.76
RZB




IP
40

IK
02

Series: Douala Kristall Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: brushed stainless steel. Crystal glass: transparent, matt inside. Glass fastening: spring system. LEDs included. Available Colours: brushed stainless steel Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 340, H 86 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1350lm System power: 24W Beam Angle: 116° Number of fittings B10A: 12 Number of fittings B16A: 20 Inrush current: 30A Unified Glare Ratio: 20,0 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	1350 lm	LOR	100%
Luminous efficacy	56 lm/W	ULOR	4%
		Total power	24 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.15 in
Diameter: 13.39 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 40
IK: 02