


Product data sheet

SIRIUS 1200 - CC GROUND RECESS
9067-B-2-688-01
UNILAMP




Description SIRIUS a brand new linear light family features various mounting application types including in-ground walk over, wall mounted, ceiling mounted, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	8.6 W	LOR	98%
Lamp flux	1054 lm	ULOR	98%
Luminous efficacy	123 lm/W	Total flux	1034 lm
CCT	4000 K	Total power	8.6 W
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	9 W	LOR	98%
Lamp flux	272 lm	ULOR	98%
Luminous efficacy	30 lm/W	Total flux	267 lm
CCT	0 K	Total power	9 W
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	8.2 W	LOR	98%
Lamp flux	923 lm	ULOR	98%
Luminous efficacy	113 lm/W	Total flux	905 lm
CCT	8000 K	Total power	8.2 W
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	6.8 W	LOR	98%
Lamp flux	372 lm	ULOR	98%
Luminous efficacy	55 lm/W	Total flux	364 lm
CCT	0 K	Total power	6.8 W
CRI	-36		

Mounting mode

Floor recessed

Shape and measurements

Length: 46.95 in

Width: 3.70 in

Height: 5.41 in

Adjustability

Fixed

Electric

System power: 32.6 W

Appliance Class: III

Protection

IP: 67

IK: 10