
## Product data sheet

EVA II 9.898.3066.05 LEIPZIGER LEUCHTEN



For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistent, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


Light output 1



## 1 x High pressure mercury vapour lamp

IP 55

Nominal lamp power	125 W	LOR	59%
Lamp flux	6800 lm	ULOR	14%
Luminous efficacy	29 lm/W	Total flux	4016 lm
CCT	3400 K	Total power	137 W
CRI	54		



## 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	59%
Lamp flux	4000 lm	ULOR	14%
Luminous efficacy	27 lm/W	Total flux	2362 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode	Electric
Pole top mounted	System power: 89-137 W
Shape and measurements	Protection
Height: 17.72 in	IP: 55
Diameter: 15.75 in	