


Product data sheet

MIC 9 STANDING MOUNTED FLOODLIGHTS
MI-50463-N-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear installed in the spigot cover

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	52.2 W	CRI	80
Total flux	6032 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	52.2 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 32.09 in
Diameter: 10.24 in
Weight: 6.8 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 52.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C