


Product data sheet

DKN QUADRAT
10434.002.1
RZB




IP
40

IK
02

Series: DKN-Quadrat, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 280, B 280, H 105 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 860lm System power: 18W Beam Angle: 130° Unified Glare Ratio: 17,0 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	860 lm	LOR	100%
Luminous efficacy	48 lm/W	ULOR	23%
		Total power	18 W

Mounting mode

Wall mounted

Shape and measurements

Length: 11.02 in
Width: 11.02 in
Height: 4.13 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 40
IK: 02