


# Product data sheet

MIC 4 BRACKET MOUNTED FLOODLIGHTS  
MI-50423-M-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 135,000, > 50,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing with a chemical chromatised protection before powder coating, ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.1 W	CRI	80
Total flux	3980 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	37.1 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 26.06 in  
Diameter: 7.76 in  
Weight: 4 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 37.1 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 07  
Surface temperature: 40°C