

Product data sheet

FLAT POLYMERO
311518.002.1
RZB




IP
40

IK
03

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, H 120 Lamp: LED Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2200lm System power: 28W Beam Angle: 116° Number of fittings B10A: 5 Number of fittings B16A: 13 Number of fittings C10A: 14 Number of fittings C16A: 22 Inrush current: 20A Unified Glare Ratio: 19,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	28 W	CRI	80
Total flux	2200 lm	LOR	100%
Luminous efficacy	79 lm/W	ULOR	10%
		Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 40
IK: 03