


# Product data sheet

TRUSYS® PERFORMANCE NARROW 50 W 4000 K DALI  
4058075291096  
LEDVANCE



Luminaire inserts with narrow light distribution. Product features: Beam angle narrow: 60°. Click into place solution with smart click buttons. Luminous efficacy: up to 160 lm/W. Fixed luminare taps. Lumen package 5600 lm, 8000 lm, 11200 lm. Steel-sheet housing. Lens material: PMMA. Type of protection: IP20. Common family design with LEDVANCE. Lifetime (L80/B10): up to 60,000 h. Product benefits: Directed light distribution for high heights. Easy installation, no tools required for connection. Energy saving and cost-effective. Flexible application due to a range of different lumen packages and beam angles. Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible. Versions with DALI ECG available. Areas of application: Direct replacement for luminaires with fluorescent lamps. Industry halls, high rack warehouse, garages, hardware stores. Equipment / Accessories: Mounting rail with fixed integrated 5- and 8-pole cable.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	80
Total flux	8000 lm	LOR	100%
Luminous efficacy	160 lm/W	Total power	50 W

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 59.06 in  
Width: 2.63 in  
Height: 1.55 in  
Weight: 1.66 kg

## Adjustability

Fixed

## Design

Material impression: Stainless steel  
Color of housing: White

## Electric

System power: 50 W  
Appliance Class: I

## Protection

IP: 20  
IK: 04  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -13...104°F