


Product data sheet

LIGHT LINEAR PT WALL AREA LUMINAIRES
LI-30022-LC-ME-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.3 W	CRI	80
Total flux	4561 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	37.3 W

Mounting mode

Wall mounted

Shape and measurements

Length: 11.42 in
Width: 7.87 in
Height: 3.15 in
Weight: 4.9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 37.3 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C