

# Product data sheet


LOUIS I (W. SHIELD ON SIDE FACING BUILDING)  
9.615.1032.27  
LEIPZIGER LEUCHTEN



IP  
55

Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	50%
Lamp flux	7200 lm	ULOR	13%
Luminous efficacy	40 lm/W	Total flux	3568 lm
CCT	3000 K	Total power	89 W
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 23.23 in  
Diameter: 7.87 in

## Electric

System power: 89 W

## Protection

IP: 55