

Product data sheet

PURA SPOT R MAXI
911365.004
RZB




IP
20

IK
03


Series: Pura Spot R Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 65° vertically, spring fastening with no need for tools, heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools, passive cooling. LED included together with connected converter in separate gearbox. Available Colours: silver Type of Installation: Recessed ceiling mounting Dimensions: L 360, B 180, H 50, HE 170 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3100K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 7400lm System power: 90W Beam Angle: 55° Number of fittings B10A: 7 Number of fittings B16A: 12 Inrush current: 32A Unified Glare Ratio: 21,6 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	45 W	CRI	90
Total flux	3700 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	45 W

Light output 2 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	45 W	CRI	90
Total flux	3700 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	45 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.09 in

Width: 14.17 in

Height: 6.06 in

Electric

System power: 90 W

Protection

IP: 20

IK: 03

Adjustability

Rotatable, Tilttable