

# Product data sheet

FLAT POLYMERO KREIS  
311949.002.2.191  
RZB




IP  
40

IK  
10

Series: FLAT POLYMERO KREIS Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Slave luminaire. Can only be operated in combination with corresponding master luminaire. Colour: white Diameter: 300&#160;mm Height: 80&#160;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 83 System power: 13&#160;W Rated luminous flux: 1200&#160;lm Luminous efficiency: 92&#160;lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP&#160;40

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	18%
		Total power	13 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.15 in  
Diameter: 11.81 in

## Adjustability

Fixed

## Electric

System power: 13 W

## Protection

IP: 40  
IK: 10