

Product data sheet


E04 CEILING ANTHRACITE
E04005
LUCEPLAN




IP
20

Apparecchi a soffitto in due diametri (70 mm e 134 mm) e differenti lunghezze. L'elemento di chiusura, realizzato in alluminio lucidato, in contrasto con la finitura esterna del corpo, conferisce all'oggetto leggerezza evidenziando il dettaglio del sistema di chiusura a filo. La posizione arretrata della sorgente aumenta l'angolo di schermatura e il comfort luminoso.


Light output 1




1 x LED			
Nominal lamp power	7 W	Socket	Gu5.3
Lamp flux	325 lm	LOR	106%
Luminous efficacy	49 lm/W	Total flux	345 lm
CCT	3000 K	Total power	7 W
CRI	80		



1 x LED			
Nominal lamp power	7 W	Socket	Gu5.3
Lamp flux	330 lm	LOR	89%
Luminous efficacy	42 lm/W	Total flux	293 lm
CCT	3000 K	Total power	7 W
CRI	80		




1 x LED			
Nominal lamp power	7 W	Socket	Gu5.3
Lamp flux	345 lm	LOR	76%
Luminous efficacy	38 lm/W	Total flux	263 lm
CCT	3000 K	Total power	7 W
CRI	80		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	630 lm	LOR	100%
Luminous efficacy	18 lm/W	Total flux	630 lm
CCT	3000 K	Total power	35 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	600 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	600 lm
CCT	3000 K	Total power	35 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	865 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	865 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1025 lm	LOR	100%
Luminous efficacy	20 lm/W	Total flux	1025 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	925 lm	LOR	100%
Luminous efficacy	18 lm/W	Total flux	925 lm
CCT	3000 K	Total power	50 W
CRI	100		

Mounting mode

Ceiling mounted

Electric

System power: 7-50 W

Shape and measurements

Length: 2.75 in

Width: 2.75 in

Height: 10.98 in

Protection

IP: 20

Adjustability

Fixed