


Product data sheet

ZIP PRO MINI 3 CIRCUIT BLACK 16W LED 3000K RA>90
5046003467
SG ARMATUREN



Three-phase rail spot with integrated powerful LED chip and driver. Dimmable with phase dimmer. Mounted using global multi-adapter, which is ideal for SG's three-phase rail system as well as other systems where Global can be used. Perfect colour rendering due to very high RA value and SDCM 2. ZIP Pro Mini is made of powder-coated aluminium, flexible and able to be pointed in almost all directions, making it the obvious choice for all places where spots or effect lighting is to be used. Light distribution Direct Light technic LED (not exchangeable) 16W (System wattage: 19W) 3000K or 4000K Ra>90 SDCM: 2 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II IP20 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004), Matt white (RAL 9003) or Silver Optics: Glass Mounting/Connection Surface, Indoor (Tracking)

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	90
Total flux	1280 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	19 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 2.95 in
Width: 1.18 in
Height: 5.60 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black, White

Electric

System power: 19 W
Appliance Class: II

Protection

IP: 20