


Product data sheet

CLARA IV (OPAL ATTACHMENT)
9.764.3042.00
LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 4.00 – 5.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately (see standard poles from p. 258) -With adapter for concrete pole consisting of flange plate made of hot galvanized steel, and transition piece made of corrosionresistant cast aluminium

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	59%
Lamp flux	4000 lm	ULOR	14%
Luminous efficacy	26 lm/W	Total flux	2356 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Electric

System power: 89 W

Shape and measurements

Height: 22.83 in
Diameter: 29.53 in