


Product data sheet

ECOLINE OFFICE 1200 WHITE 2330LM 3000K RA>80 DALI
5703821176170
SG ARMATUREN



Luminaire suspended/surface-mounted directly in 3000 or 4000 Kelvin LED. Flat design, powder-coated white RAL9010 gloss 25. Double parabolic reflector and diffuser with option of dimmable solution (DALI/SwitchDim). Plug-and-play solution for quick installation. Adjustable wire suspension (2x2 m) ordered as accessory. Light Distribution Direct Light technic LED 18W 3000K Ra>80 SDCM: 3 L80/B10 >50.000 hrs Control/Dimming DALI Protection Class I IP20 Materials and finish Housing: Sheet steel Colour: White (Pure white, 25% gloss) Optics: Double parabolic louvre, satin matt, Aluminium Mounting/Connection Suspended or surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 17, B16: 28, C10: 27, C16: 45

Light output 1



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 18 W | LOR | 100% |
| Lamp flux | 2330 lm | Total flux | 2331 lm |
| Luminous efficacy | 129 lm/W | Total power | 18 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 47.24 in
Width: 5.59 in
Height: 2.48 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 18 W
Appliance Class: I

Protection

IP: 20