Product data sheet

LER4B/LESQ4B LED 4" ROUND AND SQUARE CYLINDERS LSR4B10D010BZ EC4B10209024 4LBMMW1

COOPER LIGHTING








Distributions: narrow (30°), medium (50°) and wide (75°) beams, Mounting: ceiling, wall, stem, aircraft cable; Down or up/down styles, Extruded aluminum housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-4,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.9 W	CRI	100
Total flux	607 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	9.9 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in Width: 3.94 in Height: 3.94 in

Adjustability

Fixed

Electric

System power: 9.9 W

Protection

IP: 47